DATA SHEET. SCRUBBER DRYER RA 43IK 40







PERFECT SUCTION. EXTREMLY ROBUST: THE 40 LITRE CABLE MACHINE THAT GOES ON AND ON. RA 43 K 40



Practical: cleaning accessories always close at hand



Greater comfort with large wheels



Quick and easy seal changes

- The compact, mains operated scrubber dryer for continuous duty on small and medium size surfaces.
- Up close: the moulded, ergonomic operating handle and the singleaxis design provide effortless manoeuvrability in the tightest space.
- Large wheels for greater comfort and easy transport.
- O The mains operated machine is low in weight, making it the ideal solution for pressure sensitive floors.
- C Large fresh water opening with mesh insert for rapid filling without the need to open the tank cover.
- Easy to clean: the recovery tank has smooth walls and opens fully for rinsing and disinfection. HACCP compliant.

- The cover seals can be changed quickly and easily without tools.
- Compact design and removable squeegee tool for easier handling and transport.
- Exceptionally high brush pressure for perfect cleaning results.
- Simple, intuitive operation with a self-explanatory display.
- () The patented mounting system of the curved squeegee tool follows the movements of the machine and leaves no streaks even in tight turns.
- EUinted tested and certified.
- Made in Germany.





Perfect suction results even in tight turns



RA 43 K 40 1090 x 475 x 1055 mm

Working width	430 mm
Suction width	735 mm
Theoretical coverage max.	1720 m²/h
Noise level	66 dB(A)
Empty weight	65 kg
Operating weight	105 kg

ELECTRICAL DATA

L x W x H

Rated voltage	230 V
Power max.	1600 W
Mains cable	25 m

TANK

i uux	
Solution tank capacity	40
Recovery tank capacity	45 l

SUCTION

Low pressure max.	204 mbar
Air flow max.	45 l/s

BRUSHES AND PAD HOLDERS

Number	1
Speed	150 U/min
Brush pressure	36 kg

columbus