


DATA SHEET.
SCRUBBER DRYER.
RA 55|BM 60



SWITCH IN A FLASH: THE PATENTED MOUNTING SYSTEM FOR BRUSHES AND PAD HOLDERS.

RA 55|BM 60

- ❶ Especially designed for varying needs, this scrubber dryer with traction motor masters every situation and guarantees thoroughly cleaned surfaces of medium and large sizes.
- ❷ Effortless and safe to use, even over longer working times: ergonomically shaped handle bar, easy to operate control panel including a rocker function for back- and forward movements, good all-around visibility.
- ❸ Compact design; with a length of 138 cm, it fits into all standard lifts.
- ❹ Optional: Various tyre variants for optimum adaption to diverse working conditions.
- ❺ Environmentally friendly: the optional chemical dosage provides for a consistently high cleaning level with a low consumption of cleaning products.
- ❻ Excellent suction performance with minimal noise: the suction motor has noise emissions of just 61 dB(A); the optional silent version of just 58 dB(A).
- ❼ noBAC® version optional: antibacterial tanks for every kind of sites with stringent hygiene requirements according to HACCP concept or following hygiene plan.
- ❽ Extremely adaptable: the adaptive brush system sits flat on the floor also on uneven surfaces – and cleans every little centimeter with full brush pressure.
- ❾ Fast, easy and hygienic changing of brushes and pad holders: the brushes and pad holders do not only spin-off with the press of a button, they also spin-on automatically.
- ❿ DEKRA and EUnited Cleaning certified.
- ⓫ And: made in Germany.



* product shown with optional equipment

- Service-friendly: the recovery tank tilts to the side for easy access to batteries and components.




- Fresh water can be filled up in an instant – via the integrated, industry-standard system connector or via the large filling opening.



- The two-tank system guarantees hygienic cleaning and disinfection in accordance with the HACCP Concept.



- Mop, broom and additional work materials can be carried along within easy reach on the optional tool board located on the side.



RA 55|BM 60

L x B x H	1470 x 550 x 1100 mm
Working width	550 mm
Suction width	850 mm
Theoretical coverage max.	2200 m ² /h
Noise level	61 / 58* dB(A)
Empty weight	140 kg
Operating weight (160 Ah 5)	324 kg

BATTERIES/ELECTRICAL DATA

Rated voltage	24 V
Power max.	1240 W
Number of batteries	4
Capacity wet	175 Ah 5
Capacity gel	180 Ah 5

TANK

Solution tank capacity	60 l
Recovery tank capacity	60 l

SUCTION

Low pressure max.	110 mbar
Air flow max.	32 l/s

TRACTION

Power max.	300 W
Speed max.	6 km/h

BRUSHES AND PAD HOLDERS

Number	1
Speed	150 rpm
Brush pressure	30 kg

*silent version, optional.